



Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **E0002014 - E0002012 - E0002013**
Product name **Primer al Solvente**
UFI : **KN10-J0TN-T00M-72AD**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **Liquid bituminous paint. Professional, industrial.**

1.3. Details of the supplier of the safety data sheet

Name **MATCO SRL**
Full address **via Quadrelli 69**
District and Country **37055 Ronco all'Adige (VR) Italia**
Tel. **045 6608111**
Fax **045 6608177**

e-mail address of the competent person responsible for the Safety Data Sheet

info@matcosrl.com

1.4. Emergency telephone number

For urgent inquiries refer to

Marco Marano CAVp Osp. Pediatrico Bambino Gesù Roma Piazza Sant'Onofrio, 4 00165 Tel..06 68593726
Anna Lepore Az. Osp. Univ. Foggia Foggia V.le Luigi Pinto, 1 71122 Tel.800183459
Gennaro Savoia Az. Osp. A. Cardarelli Napoli Via A. Cardarelli, 9 80131 Tel. 081 5453333
M. Caterina Grassi Cav.Policlinico Umberto I Roma V.le del Policlinico, 155 161 Tel.06 49978000
Alessandro Barelli CAV Policlinico A. Gemelli Roma Largo Agostino Gemelli, 8 168 Tel.06 3054343
Primo Botti Az. Osp. Careggi U.O. Tossicologia Medica Firenze Largo Brambilla, 3 50134 Tel. 055 7947819
Carlo Locatelli CAV Centro nazionale di Informazione Tossicologia Pavia Via Salvatore Maugeri ,10 27100 Tel.0382 24444
Franca Davanzo Osp. Niguarda Cà Granda Milano Piazza Ospedale Maggiore, 3 20162 Tel.02 66101029
M. Luisa Farina Azienda Osp. Papa Giovanni XXII Bergamo Piazza OMS, 1 24127 Tel. 800883300
Azienda Ospedaliera Integrata di Verona, Piazzale Aristide Stefani,1 37126 800011858

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Flammable liquid, category 2	H225	Highly flammable liquid and vapour.
Reproductive toxicity, category 2	H361d	Suspected of damaging the unborn child.
Aspiration hazard, category 1	H304	May be fatal if swallowed and enters airways.
Specific target organ toxicity - repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Eye irritation, category 2	H319	Causes serious eye irritation.



SECTION 2. Hazards identification ... / >>

Skin irritation, category 2	H315	Causes skin irritation.
Specific target organ toxicity - single exposure, category 3	H335	May cause respiratory irritation.
Specific target organ toxicity - single exposure, category 3	H336	May cause drowsiness or dizziness.
Hazardous to the aquatic environment, chronic toxicity, category 3	H412	Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H225	Highly flammable liquid and vapour. H361d
H304	Suspected of damaging the unborn child.
H373	May be fatal if swallowed and enters airways.
H319	May cause damage to organs through prolonged or repeated exposure.
H315	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P331	Do NOT induce vomiting.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P301+P310	IF SWALLOWED: immediately call a POISON CENTER / doctor / . . .
P370+P378	In case of fire: use carbon dioxide, powder, foam to extinguish.
P261	Avoid breathing dust / fume / gas / mist / vapours / spray.

Contains: Toluene
XYLENE
N-BUTYL ACETATE
ISOBUTYL ACETATE

VOC (Directive 2004/42/EC) :

Binding primers.

VOC given in g/litre of product in a ready-to-use condition : 646,40

Limit value: 750,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.1. Substances

Information not relevant



SECTION 3. Composition/information on ingredients ... / >>

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
Oxidized bitumen f.		
INDEX	21 ≤ x < 22,5	
EC	265-196-4	
CAS	64742-93-4	
REACH Reg.	01-2119498270-36	
Toulene		
INDEX	601-021-00-3	16,5 ≤ x < 18
EC	203-625-9	Flam. Liq. 2 H225, Repr. 2 H361d, Asp. Tox. 1 H304, STOT RE 2 H373, Skin Irrit. 2 H315, STOT SE 3 H336
CAS	108-88-3	
REACH Reg.	01-2119471310-51	
XYLENE		
INDEX	16,5 ≤ x < 18	Flam. Liq. 3 H226, Acute Tox. 4 H312, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373, Eye Irrit. 2 H319, Skin Irrit. 2 H315, STOT SE 3 H335, Classification note according to Annex VI to the CLP Regulation: C
EC	905-562-9	STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l
CAS		
REACH Reg.	01-2119555267-33	
N-BUTYL ACETATE		
INDEX	607-025-00-1	15 ≤ x < 16,5
EC	204-658-1	Flam. Liq. 3 H226, STOT SE 3 H336, EUH066
CAS	123-86-4	
REACH Reg.	01-2119485493-29	
ISOBUTYL ACETATE		
INDEX	607-026-00-7	8 ≤ x < 9
EC	203-745-1	Flam. Liq. 2 H225, STOT SE 3 H336, EUH066, Classification note according to Annex VI to the CLP Regulation: C
CAS	110-19-0	
REACH Reg.	01-2119488971-22	
HIDROCARBONS, C9, AROMATICS		
INDEX	3,5 ≤ x < 4	Flam. Liq. 3 H226, Asp. Tox. 1 H304, STOT SE 3 H335, STOT SE 3 H336, Aquatic Chronic 2 H411, EUH066, Classification note according to Annex VI to the CLP Regulation: P
EC	918-668-5	
CAS		
REACH Reg.	01-2119455851-35	
ETHYL ACETATE		
INDEX	607-022-00-5	3,5 ≤ x < 4
EC	205-500-4	Flam. Liq. 2 H225, Eye Irrit. 2 H319, STOT SE 3 H336, EUH066
CAS	141-78-6	
REACH Reg.	01-2119475103-46	
ETHYLBENZENE		
INDEX	601-023-00-4	3,5 ≤ x < 4
EC	202-849-4	Flam. Liq. 2 H225, Acute Tox. 4 H332, Asp. Tox. 1 H304, STOT RE 2 H373
CAS	100-41-4	LC50 Inhalation vapours: 17,2 mg/l/4h
REACH Reg.	01-2119489370-35	
Acetonitrile ***		
INDEX	2 ≤ x < 2,5	Flam. Liq. 2 H225, Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Irrit. 2 H319
EC		STA Oral: 500 mg/kg, STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l, STA Inhalation mists/powders: 1,5 mg/l
CAS	75-05-8	
REACH Reg.	01-2119471307-38	
CYCLOHEXANONE		
INDEX	606-010-00-7	1,5 ≤ x < 2
EC	203-631-1	Flam. Liq. 3 H226, Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Eye Dam. 1 H318, Skin Irrit. 2 H315
CAS	108-94-1	STA Oral: 500 mg/kg, STA Dermal: 1100 mg/kg, STA Inhalation vapours: 11 mg/l, STA Inhalation mists/powders: 1,5 mg/l
REACH Reg.	01-2119453616-35	



SECTION 3. Composition/information on ingredients ... / >>

DIACETONE ALCOHOL

INDEX 603-016-00-1 $1,5 \leq x < 2$ Repr. 2 H361d, Eye Irrit. 2 H319, STOT SE 3 H335
EC 204-626-7
CAS 123-42-2
REACH Reg. 01-2119473975-21

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

Send away individuals who are not suitably equipped. Use explosion-proof equipment. Eliminate all sources of ignition (cigarettes, flames, sparks, etc.) from the leakage site.

6.2. Environmental precautions



SECTION 6. Accidental release measures ... / >>

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

CZE	Česká Republika	Nářizení vlády č. 41/2020 Sb. Nařizení vlády, kterým se mění nařizení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci, ve znění pozdějších předpisů
DEU	Deutschland	Technischen Regeln für Gefahrstoffe (TRGS 900) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte. MAK- und BAT-Werte-Liste 2020, Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe, Mitteilung 56
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α' 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών 2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ "σχετικά με την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή μεταλλαξιογόνους παράγοντες κατά την εργασία"»
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemičalijama na radu, graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
ROU	România	Hotărârea nr. 53/2021 pentru modificarea hotărârii guvernului nr. 1.218/2006, precum și pentru modificarea și completarea hotărârii guvernului nr. 1.093/2006
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu (Uradni list RS, št. 100/01, 39/05, 53/07, 102/10, 43/11 – ZVZD-1, 38/15, 78/18 in 78/19)
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2022



SECTION 8. Exposure controls/personal protection ... / >>

Toulene

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	200		500		SKIN
AGW	DEU	190	50	760	200	SKIN
MAK	DEU	190	50	760	200	SKIN
VLEP	FRA	76,8	20	384	100	SKIN
GVI/KGVI	HRV	192	50	384	100	SKIN
VLEP	ITA	192	50			SKIN
WEL	GBR	191	50	384	100	SKIN
OEL	EU	192	50	384	100	SKIN
TLV-ACGIH		75,4	20			
TLV-ACGIH		75,4			20	SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,68	mg/l
Normal value in marine water	0,68	mg/l
Normal value for fresh water sediment	16,39	mg/kg
Normal value for marine water sediment	16,39	mg/kg
Normal value for water, intermittent release	0,68	mg/l
Normal value of STP microorganisms	13,61	mg/l
Normal value for the terrestrial compartment	2,89	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				8,13 mg/kg/d				
Inhalation	226 mg/m3	226 mg/m3		56,5 mg/m3	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3
Skin				226 mg/kg/d				384 mg/kg/d

XYLENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	200	45,4	400	90,8	SKIN
AGW	DEU	440	100	880	200	SKIN
MAK	DEU	440	100	880	200	SKIN
VLEP	FRA	221	50	442	100	SKIN
TLV	GRC	435	100	650	150	
GVI/KGVI	HRV	221	50	442	100	SKIN
VLEP	ITA	221	50	442	100	SKIN
TLV	ROU	221	50	442	100	SKIN
MV	SVN	221	50	442	100	SKIN
WEL	GBR	220	50	441	100	SKIN
OEL	EU	221	50	442	100	SKIN
TLV-ACGIH			20			

N-BUTYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	950	196,65	1200	248,4	
AGW	DEU	300	62	600 (C)	124 (C)	
VLEP	FRA	710	150	940	200	
TLV	GRC	710	150	950	200	
GVI/KGVI	HRV	241	50	723	150	
VLEP	ITA	241	50	723	150	
TLV	ROU	241	50	723	150	
MV	SVN	300	62	600	124	
WEL	GBR	724	150	966	200	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	



SECTION 8. Exposure controls/personal protection ... / >>

ISOBUTYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	950	196,65	1200	248,4	
AGW	DEU	300	62	600 (C)	124 (C)	
VLEP	FRA	710	150	940	200	
TLV	GRC	950	200	950	200	
GVI/KGVI	HRV	241	50	723	150	
VLEP	ITA	241	50	723	150	
TLV	ROU	241	50	723	150	
MV	SVN	300	62	600	124	
WEL	GBR	724	150	903	187	
OEL	EU	241	50	723	150	
TLV-ACGIH			50		150	

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	200	45,4	500	113,5	SKIN
AGW	DEU	88	20	176	40	SKIN
MAK	DEU	88	20	176	40	SKIN
VLEP	FRA	88,4	20	442	100	SKIN
TLV	GRC	435	100	545	125	
GVI/KGVI	HRV	442	100	884	200	SKIN
VLEP	ITA	442	100	884	200	SKIN
TLV	ROU	442	100	884	200	SKIN
MV	SVN	442	100	884	200	SKIN
WEL	GBR	441	100	552	125	SKIN
OEL	EU	442	100	884	200	SKIN
TLV-ACGIH		87	20			

ETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	700	191,1	900	245,7	
AGW	DEU	730	200	1460	400	
MAK	DEU	750	200	1500	400	
VLEP	FRA	734	200	1468	400	
TLV	GRC	734	200	1468	400	
GVI/KGVI	HRV	734	200	1468	400	
VLEP	ITA	734	200	1468	400	
TLV	ROU	734	200	1468	400	
MV	SVN	734	200	1468	400	
WEL	GBR	734	200	1468	400	
OEL	EU	734	200	1468	400	
TLV-ACGIH		1441	400			



SECTION 8. Exposure controls/personal protection ... / >>

DIACETONE ALCOHOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	200	41,4	300	62,1	
AGW	DEU	96	20	192	40	SKIN
MAK	DEU	96	20	192	40	SKIN
VLEP	FRA	240	50			
TLV	GRC	240	50	360	75	
GVI/KGVI	HRV	241	50	362	75	
TLV	ROU	150	32	250	53	
MV	SVN	96	20	192	40	SKIN
WEL	GBR	241	50	362	75	
TLV-ACGIH		238	50			

Predicted no-effect concentration - PNEC

Normal value in fresh water	2	mg/l
Normal value in marine water	0,2	mg/l
Normal value for fresh water sediment	7,4	mg/kg/d
Normal value for marine water sediment	0,74	mg/kg/d
Normal value for water, intermittent release	1	mg/l
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	0,31	mg/kg/d

CYCLOHEXANONE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	CZE	40	9,8	80	196	SKIN
AGW	DEU	80	20	80	20	SKIN
VLEP	FRA	40,8	10	81,6	20	
TLV	GRC	200	50	400	100	
GVI/KGVI	HRV	40,8	10	81,6	20	SKIN
VLEP	ITA	40,8	10	81,6	20	SKIN
TLV	ROU	40,8	10	81,6	20	SKIN
MV	SVN	40,8	10	81,6	20	SKIN
WEL	GBR	41	10	82	20	SKIN
OEL	EU	40,8	10	81,6	20	SKIN
TLV-ACGIH		80	20	201	50	SKIN

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

Aromatic hydrocarbon, C9 hydrocarbons, aromatics

Two/8h 100mg/m3 19 ppm stel/15min

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

Consider the appropriateness of providing antistatic clothing in the case of working environments in which there is a risk of explosion.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).



SECTION 8. Exposure controls/personal protection ... / >>

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	black	
Odour	characteristic	
Melting point / freezing point	not available	
Initial boiling point	> 65 °C	
Flammability	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Flash point	< 23 °C	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
pH	not available	
Kinematic viscosity	not available	
Solubility	insoluble in water	
Partition coefficient: n-octanol/water	not available	
Vapour pressure	0,94 mmHg	
Density and/or relative density	0,90-0,98	
Relative vapour density	not available	
Particle characteristics	not applicable	

9.2. Other information

nd.

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Dry residue $\geq 22\%$

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

N-BUTYL ACETATE

Decomposes on contact with: water.

ISOBUTYL ACETATE

Decomposes under the effect of heat. Attacks various types of plastic materials.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.



SECTION 10. Stability and reactivity ... / >>

DIACETONE ALCOHOL

Decomposes at temperatures above 90°C/194°F.

CYCLOHEXANONE

Attacks various types of plastic materials.

May condense under the effect of heat to form resinous compounds.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

XYLENE

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

ISOBUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react violently with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

DIACETONE ALCOHOL

Risk of explosion on contact with: air, sources of heat. May react dangerously with: alkaline metals, amines, oxidising agents, acids.

CYCLOHEXANONE

Risk of explosion on contact with: hydrogen peroxide, nitric acid, heat, mineral acids. May react violently with: oxidising agents. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

ISOBUTYL ACETATE

Avoid exposure to: sources of heat, naked flames.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

DIACETONE ALCOHOL

Avoid exposure to: light, sources of heat, naked flames.

CYCLOHEXANONE

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

ISOBUTYL ACETATE

Incompatible with: strong oxidants, nitrates, strong acids, strong bases.

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, aluminium, nitrates, chlorosulphuric acid. Incompatible materials: plastic materials.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.



SECTION 11. Toxicological information ... / >>

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

XYLENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

DIACETONE ALCOHOL

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

XYLENE

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

DIACETONE ALCOHOL

Acute toxicity causes irritation of the eyes, nose and throat in humans at 100 ppm (476 mg/kg) and pulmonary disorders at 400 ppm.

No chronic effects on humans have been reported. The substance may have a depressive effect on the respiratory centres and cause death from respiratory failure.

Interactive effects

XYLENE

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY

ATE (Inhalation - mists / powders) of the mixture:	> 5 mg/l
ATE (Inhalation - vapours) of the mixture:	> 20 mg/l
ATE (Inhalation - gas) of the mixture:	0,0 mg/l
ATE (Oral) of the mixture:	>2000 mg/kg
ATE (Dermal) of the mixture:	>2000 mg/kg



SECTION 11. Toxicological information ... / >>

Toulene
LD50 (Dermal): 12267 mg/kg rabbit
LD50 (Oral): 5000 mg/kg 24h rat
LC50 (Inhalation vapours): 25,7 mg/l/4h rat

XYLENE
LD50 (Dermal): 4350 mg/kg Rabbit
STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
3523 mg/kg Rat
LD50 (Oral): 3523 mg/kg Rat
LC50 (Inhalation vapours): 26 mg/l/4h Rat
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

N-BUTYL ACETATE
LD50 (Dermal): > 5000 mg/kg Rabbit
LD50 (Oral): > 6400 mg/kg Rat
LC50 (Inhalation vapours): 21,1 mg/l/4h Rat

ETHYLBENZENE
LD50 (Dermal): 15354 mg/kg Rabbit
LD50 (Oral): 3500 mg/kg Rat
LC50 (Inhalation vapours): 17,2 mg/l/4h Rat

Acetonitrile ***
STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
STA (Inhalation mists/powders): 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

DIACETONE ALCOHOL
LD50 (Dermal): 2 ml/kg ratto-Coniglio DL 50 13,75 mg/Kg
LD50 (Oral): 3 g/kg Rat
LC50 (Inhalation vapours): 7,6 mg/l/4h su animale

CYCLOHEXANONE
STA (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
STA (Dermal): 1100 mg/kg estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
STA (Inhalation mists/powders): 1,5 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)
STA (Inhalation vapours): 11 mg/l estimate from table 3.1.2 of Annex I of the CLP
(figure used for calculation of the acute toxicity estimate of the mixture)

Aromatic hydrocarbon, C9 hydrocarbons, aromatics
Hydrocarbons, aromatic c9 oral LD50 3492 mg/kg/rat ld50cuanea <3160 mg/kg rabbit lc50 inhalation> 6193 mg/m3rat

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY



SECTION 11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

XYLENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Suspected of damaging the unborn child

STOT - SINGLE EXPOSURE

May cause respiratory irritation
May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Toxic for aspiration

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

Aromatic hydrocarbon, C9 hydrocarbons, aromatics

LC50 Pisces 9.2 mg/96h EC50 Crustacean fish 3.2 mg/148h EI50 Daphnia Magna Ec50 Algae/Aquatic plants 2.9 mg/l/72h
EL50PSEUDOKIGKERNIELLAGNELLA SUBCAPIATED

DIACETONE ALCOHOL

LC50 - for Fish	> 100 mg/l/96h oryza latipes
EC50 - for Crustacea	> 1000 mg/l/48h pulce d'acqua grande
EC50 - for Algae / Aquatic Plants	> 1000 mg/l/72h pseudokirchneriella subcapitata
Chronic NOEC for Crustacea	100 mg/l 21d
Chronic NOEC for Algae / Aquatic Plants	1000 mg/l 72h

Toulene

LC50 - for Fish	5,5 mg/l/96h Oncorhynchus kisutch
EC50 - for Crustacea	3,78 mg/l/48h Ceriodaphnia dubia
EC50 - for Algae / Aquatic Plants	134 mg/l/72h Chlamydomonas angulosa
Chronic NOEC for Fish	1,39 mg/l 40 giorni - Oncorhynchus kisutch
Chronic NOEC for Crustacea	0,74 mg/l 7 giorni - Ceriodaphnia dubia
Chronic NOEC for Algae / Aquatic Plants	10 mg/l 72 ore - Skeletonema costatum

12.2. Persistence and degradability

XYLENE

Solubility in water	100 - 1000 mg/l
Rapidly degradable	



SECTION 12. Ecological information ... / >>

ETHYLBENZENE	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
DIACETONE ALCOHOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
CYCLOHEXANONE	
Solubility in water	0,1 - 100 mg/l
Rapidly degradable	
ETHYL ACETATE	
Solubility in water	> 10000 mg/l
Rapidly degradable	
N-BUTYL ACETATE	
Solubility in water	1000 - 10000 mg/l
ISOBUTYL ACETATE	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
Toulene	
Rapidly degradable	Rapidamente Biodegradabile

12.3. Bioaccumulative potential

XYLENE	
Partition coefficient: n-octanol/water	3,12
BCF	25,9
ETHYLBENZENE	
Partition coefficient: n-octanol/water	3,6
DIACETONE ALCOHOL	
Partition coefficient: n-octanol/water	-0,09
CYCLOHEXANONE	
Partition coefficient: n-octanol/water	0,86
ETHYL ACETATE	
Partition coefficient: n-octanol/water	0,68
BCF	30
N-BUTYL ACETATE	
Partition coefficient: n-octanol/water	2,3
BCF	15,3
ISOBUTYL ACETATE	
Partition coefficient: n-octanol/water	2,3
BCF	15,3
Toulene	
BCF	90

12.4. Mobility in soil

XYLENE	
Partition coefficient: soil/water	2,73
CYCLOHEXANONE	
Partition coefficient: soil/water	1,18
N-BUTYL ACETATE	
Partition coefficient: soil/water	< 3



SECTION 12. Ecological information ... / >>

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

Waste transportation may be subject to ADR restrictions.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

14.1. UN number or ID number

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL MIXTURE
 IMDG: PAINT or PAINT RELATED MATERIAL MIXTURE
 IATA: PAINT or PAINT RELATED MATERIAL MIXTURE

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3

IMDG: Class: 3 Label: 3

IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO
 IMDG: NO
 IATA: NO

14.6. Special precautions for user

ADR / RID:	HIN - Kemler: 33 Special provision: -	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
IMDG:	EMS: F-E, <u>S-E</u>	Limited Quantities: 5 L	Packaging instructions: 364
IATA:	Cargo: Passengers: Special provision:	Maximum quantity: 60 L Maximum quantity: 5 L A3, A72	Packaging instructions: 353





SECTION 14. Transport information ... / >>

14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: P5c

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3 - 40

Contained substance

Point 75

Point 48 Toulene
REACH Reg.: 01-2119471310-51

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage \geq than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC):

Binding primers.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

Toulene

XYLENE

N-BUTYL ACETATE

ETHYL ACETATE

DIACETONE ALCOHOL

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Flam. Liq. 2	Flammable liquid, category 2
Flam. Liq. 3	Flammable liquid, category 3
Repr. 2	Reproductive toxicity, category 2
Acute Tox. 4	Acute toxicity, category 4
Asp. Tox. 1	Aspiration hazard, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
Aquatic Chronic 2	Hazardous to the aquatic environment, chronic toxicity, category 2
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H225	Highly flammable liquid and vapour.



SECTION 16. Other information ... / >>

H226	Flammable liquid and vapour.
H361d	Suspected of damaging the unborn child.
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)



SECTION 16. Other information ... / >>

20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 08 / 09 / 11 / 12 / 15 / 16.